

ITED STATES PATENT AND TRADEMARK OFFICE

In re the Application of

Hiroshi ISONO

Group Art Unit: 3683

Application No.: 09/833,763

Examiner:

B. KING

Filed: April 13, 2001

Docket No.: 109246

For:

BRAKING SYSTEM HAVING VALVE DEVICE FOR DELIVERING PRESSURIZED

FLUID TO BRAKE CYLINDER SELECTIVELY FROM AT LEAST TWO

PRESSURIZING CHAMBERS OR ONLY ONE OF THEM

INFORMATION DISCLOSURE STATEMENT

Commissioner for Patents P.O. Box 1450 Alexandria, VA 22313-1450

Sir:

Pursuant to 37 CFR §1.56, the attention of the Patent and Trademark Office is hereby directed to the references listed on the attached PTO-1449. Unless otherwise indicated herein, one copy of each reference is attached. It is respectfully requested that the information be expressly considered during the prosecution of this application, and that the references be made of record therein and appear among the "References Cited" on any patent to issue therefrom.

- This Information Disclosure Statement is being filed more than three months after \bowtie 1. the U.S. filing date AND after the mailing date of the first Office Action on the merits, but before the mailing date of a Final Rejection, Notice of Allowance or other action that closes prosecution (e.g., Quayle Action).
 - Attached is our Check No. 183088 in the amount of \$180.00 in payment \boxtimes of the fee under 37 CFR §1.17(p). Please credit or debit Deposit Account No. 15-0461 as needed to ensure consideration of the disclosed information. Two duplicate copies of this paper are attached.
- In accordance with 37 CFR §1.98(a)(2)(ii), copies of any U.S. patents and patent \boxtimes application publications are not attached.

08/16/2006 SDEHBOB1 00000140 09833763 01 FC:1886 180.00 NP 3. A concise explanation of the relevance of one or more non-English language reference cited herein appears in the Appendix attached hereto. See References 2-5.

Respectfully submitted,

James A. Oliff

Registration No. 27,075

Scott M. Schulte

Registration No. 44,325

JAO:SMS/sxb

Date: August 15, 2006

OLIFF & BERRIDGE, PLC P.O. Box 19928 Alexandria, Virginia 22320 Telephone: (703) 836-6400 DEPOSIT ACCOUNT USE
AUTHORIZATION
Please grant any extension
necessary for entry;
Charge any fee due to our
Deposit Account No. 15-0461

Sheet	1	of	1	

Form PTO-1449 US Dept. of Commerce (REV. 1/06) PATENT & TRADEMARK OFFICE		ATTY DOCKET NO. 109246			APPLICATION NO. 09/833,763					
P.E. 4	INFORMA	ATION DISCLOSURE STATEMENT								
	(Use covered cheets if necessary)				APPLICANT(S) Hiroshi ISONO					
WANG-19	NIG-1 5 2006			FILING DATE April 13, 2001			GROUP 3683			
TO TRAD			U.S. PATEN	T DOCUI	MENTS					
Examiner Initials	Cite No.			Date		Name	Name			
	1	2,587,023	02/26/19	952	ALLYN					
	-			_						
	<u> </u>	FC	DREIGN PAT	ENT DO	L					
Examiner Initials	Cite No.			ate	Country		With English Abstract	With English Translation		
	2	WO 97/26168 A1 07		97	WIPO					
	3 DE 199 21 478 A1 4 DE 44 25 578 A1 5 DE 24 36 059 A1		11/9/2000 01/25/1996		GERMANY					
					GERMANY					
			A1 02/05/19		GERMANY					
	<u> </u>									
	1	T	OTHER D							
Examiner Initials	Cite No.	(Including Author, Title, Date, Pertinent Pages, etc.)								
· · · · · · · · · · · · · · · · · · ·				· · -						
EXAMINER						DATE C	ONSIDERED)		
Examiner:	Initial if	citation considered, whether or not ci	tation is in co	onformano	te with M.P.E.P. 609; draw lin	ne through cit	ation if not in	conformance		
	and not	considered. Include copy of this form	WITH HEXT COIL	municati	on to applicant.					

Date: August 15, 2006

APPENDIX

WO 97/26168A1 shows stepped piston 22 disposed between return pump 14 and brake cylinder 5, for fast filling of pressurized fluid to the brake cylinder 5.

DE 19921478 A1 shows preliminary pressure generator 9 for applying preliminary pressure to brake cylinders 2, 3 for fast filling of the brake cylinders, while shut-off valve 10 is closed.

DE 4425578 A1 shows brake booster 5 for pre-filling of brakes 17, 18 before the brakes are operated by return pump 7.

DE 2436059 A1 shows master cylinder including plunger piston 2, and annular piston 7a which is moved together with the plunger piston 2 under biasing force of spring 9 during an initial operation of brake operating member 1, for fast filling of brake cylinder. The master cylinder has only one pressurizing chamber 4.